

40X40X10 mm

KF0410-03 Series

- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$



SPECIFICATIONS												
Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)	
KF0410B5H-03	Dual Ball	5	4.25~5.75	6.42	0.129	6000	0.13	0.65	0.8	26.4	15	
KF0410B5M-03				5.75	0.106	5400	0.09	0.45	0.5	24.4		
KF0410B5L-03				4.37	0.067	4200	0.07	0.35	0.4	19.9		
KF0410-5H-03	S,H			6.42	0.129	6000	0.20	1.00	1.2	26.4		
KF0410-5M-03				5.75	0.106	5400	0.10	0.50	0.8	24.4		
KF0410-5L-03				4.37	0.067	4200	0.08	0.40	0.6	19.9		
KF0410B1H-03	Dual Ball	12	10.2~13.8	6.42	0.129	6000	0.07	0.84	0.8	26.4		
KF0410B1M-03				5.75	0.106	5400	0.06	0.72	0.7	24.4		
KF0410B1L-03				4.37	0.067	4200	0.05	0.60	0.6	19.9		
KF0410-1H-03	S,H			6.42	0.129	6000	0.08	0.96	1.2	26.4		
KF0410-1M-03				5.75	0.106	5400	0.07	0.84	0.8	24.4		
KF0410-1L-03				4.37	0.067	4200	0.06	0.72	0.7	19.9		
KF0410B2S-03	Dual Ball	24	20.4~27.6	6.97	0.159	6600	0.06	1.44	1.4	29.3		
KF0410B2H-03				6.42	0.129	6000	0.05	1.20	1.2	26.4		
KF0410B2M-03				5.75	0.106	5400	0.04	0.96	1.0	24.4		
KF0410B2L-03				4.37	0.067	4200	0.03	0.72	0.8	19.9		
KF0410-2H-03				S,H	6.42	0.129	6000	0.05	1.20	1.2		26.4
KF0410-2M-03					5.75	0.106	5400	0.04	0.96	1.0		24.4
KF0410-2L-03	4.37	0.067	4200	0.03	0.72	0.8	19.9					

Specifications subject to change without notice

The 7TH character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

